

Nonius Hanger set – Upper Part, Bottom Part, Bracket, Connector and Extension

Description:

Nonius hanger set for direct suspension of CD 60 Premium profile ceiling system to the structural ceiling (concrete, timber, etc.), in cases of greater suspension heights and increased load-bearing capacity requirements. It provides a durable and secure connection with load class 0,40 kN.



Nonius Hanger, Upper Part has multiple pre-cut service holes along its length and four standard lengths of 120, 360, 460, 960 mm to ensure wide variety of suspension heights. It provides the connection between the structural soffit and **Nonius Hanger, Bottom Part**
Metal thickness: 1.0 mm



Connector for Nonius Hanger enables the connection of **Nonius Hanger Upper Part** and **Extension for Nonius Hanger**.
Metal thickness: 1.0 mm



Extension for Nonius Hanger connects securely **Nonius Hanger Upper Part** and **Nonius Hanger Bottom Part** in cases of suspended ceilings with particularly large suspension heights.
Metal thickness: 1.0 mm



Nonius Hanger, Bracket – For secure connection of the individual Nonius components. With the **Nonius Hanger Bracket**, Nonius suspensions can be easily and securely fixed and readjusted.
Metal thickness: Ø 2.5 mm



Nonius Hanger, Bottom Part - the specially designed T-shaped bottom part with arms for direct fixation to the CD 60 profile provides optimal strength. The upper part has pre-cut service holes for increased precision in leveling of the construction.
Metal thickness: 1.0 mm



The grey-colored zinc coating guarantees vast corrosion resistance of the element.

Standard Classification:

In compliance with **EN 13964:2014**



Advantages:

- ✓ Ensures a stable and rigid connection of the suspended ceiling system to the main structure
- ✓ Suitable for fire protection requirements
- ✓ Increased load-bearing capacity of up to 0.4 kN
- ✓ Pre-cut service holes for increased precision in levelling of suspended ceilings and providing wide variety of suspension heights
- ✓ Enables the installation of suspended ceilings with particularly large suspension heights
- ✓ Quick and easy application

Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.40 kN

Packaging and Storage:

Product	Length	Thickness	Box
Nonius hanger Upper part 120	120 mm	1.0 mm	100 pcs
Nonius Hanger Upper part 360	360 mm	1.0 mm	100 pcs
Nonius Hanger Upper part 460	460 mm	1.0 mm	50 pcs
Nonius Hanger Upper part 960	960 mm	1.0 mm	25 pcs
Connector for Nonius Hanger 100 mm	100 mm	1.0 mm	100 pcs
Extension for Nonius Hanger 1000 mm	1000 mm	1.0 mm	25 pcs
Nonius Hanger Bracket	70 mm	Ø 2.5 mm	100 pcs
Nonius Hanger Bottom part	150 mm	1.0 mm	100 pcs

- ✓ Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered, and ventilated area

Safety Recommendations:

- ✓ Product not classified as hazardous.
- ✓ To prevent physical harm, the use of safety gloves is strongly advisable when working with this product.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. 2024©