TrennFix Separation Strip 65 mm



Description:

Special TrennFix separation strip for a crack-free transition between dry construction systems and solid elements of the buildings.

The TrennFix tape has a 10mm self-adhesive strip on one side that allows the separation of the two surfaces.

Advantages:

- ✓ Easy to use.
- ✓ Dimensionally stable even at high humidity.
- ✓ Removable without residue.

Application:

- ✓ For a crack-free transition between dry construction systems and the solid part of the building.
- ✓ For transition between surfaces with gypsum plaster.

Instructions for use:

1. The structure built of Premium CW / UW or UD Technogips Pro profiles is installed.
2. Trenn-Fix separation strip is glued to Premium CW/UW or UD profiles Technogips Pro with the self-adhesive side.
3. The gypsum plasterboards with a distance of about 5 mm on the other side of the Trenn-Fix separation strip are installed. The joint is filled and leveled.
4. After drying, the excess Trenn-Fix separation strip should be cut off and removed.

Technical Data:

Parameters:	
Width	65 mm
Thickness	50 µm

Packaging and Storage:

Product	Length	rolls/box
TrennFix Separation Strip 65 mm	50 m	24 pcs

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered, and ventilated area

Safety recommendations:

- ✓ Product is not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. 2024©