

Drywall Screw TN

for plasterboard

DESCRIPTION

Drywall Screw TN, designed with needle point tip, fine thread and bugle head for mounting plasterboard to metal sheet profiles with gauge up to 0.7 mm.

Manufactured from hardened carbon steel with a protective phosphate coating, ensuring a quick, easy and secure installation and long-lasting connection.

The screw is suitable for interior applications in premium drywall system solutions Technogips Pro .



QUALITY GUARANTEE

CE¹⁸ In compliance with **EN 14566:2008**
In compliance with **DIN 18182-2** Type **TN**

TECHNICAL DATA

Material	Carbon Steel
Coating	Grey Phosphate
Reaction to fire	A1
Protection against corrosion	48 hrs
Drilling time	< 2 sec.
Pull-out resistance	≥ 450 N
Thread	Fine
Profile penetration	≥ 10 mm

ADVANTAGES

- ✓ Needle point tip and fine thread for effortless drilling
- ✓ Phosphate coating for reliable and durable protection in case of short-term contact with moisture
- ✓ Countersunk head that sits flush creating smooth, clean, ready-to-finish surface
- ✓ PH 2 screw bit in every box

DIMENSIONS AND PACKAGING

PRODUCT	DIAMETER (mm)	LENGTH (mm)	BIT	BOX (pcs)	BOXES IN CARTON (pcs)
Drywall Screw TN 3.5x25	3.5	25	PH2	1000	16
Drywall Screw TN 3.5x35	3.5	35	PH2	1000	12
Drywall Screw TN 3.5x45	3.5	45	PH2	500	16
Drywall Screw TN 3.5x55	3.5	55	PH2	500	12
Drywall Screw TN 4.2x70	4.2	70	PH2	250	12

- ✓ Packaged in distinctive green Technogips Pro boxes with included PH2 screw bit.
- ✓ Store in a dry, well-ventilated area.


Drywall Screw TN

for plasterboard

APPLICATION

Suitable for application in interior drywall construction systems
Technogips Pro:

- ✓ Partition walls
- ✓ Wall linings
- ✓ Shaft walls
- ✓ Suspended ceilings
- ✓ And others



Depending on the screw length, Drywall Screw TN is suitable for mounting one to four layers of plasterboards to metal studs with metal sheet thickness up to 0.7 mm.

SCREW LENGTH APPLICATION

BOARD THICKNESS	FIRST LAYER	SECOND LAYER	THIRD LAYER	FOURTH LAYER
9.5 mm	3.5 x 25	3.5 x 35	x	x
12.5 mm	3.5 x 25	3.5 x 35	3.5 x 55	4.2 x 70
15.0 mm	3.5 x 25	3.5 x 45	3.5 x 55	4.2 x 70

SAFETY RECOMMENDATIONS

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro manufactures and develops a wide range of construction products for various applications divided into the following product categories:

- ✓ Drywall System Solutions;
- ✓ Lightweight Facade Systems;
- ✓ Systems for fire protection and sound insulation;
- ✓ Gypsum-based plasters and finishes;

Technogips Pro also provides various technical information such as CAD details, detailed technical statements, specification clauses, application manuals and technical support both for contractors and consultants' offices as well as construction sites visits. For further information on our products and systems kindly check our website or contact your local Technogips Pro representative.

Formatt Building Products Ltd.

Office address

Sofia 1404,

49B Bulgaria Blvd,

www.technogipspro.com

sales@technogipspro.com

FORMATT

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification.

2025©